

1000 CAMEL X-CNC (version 2)

Automatic two column band saw machine with complete hydraulic control. The machine is designed for vertical cuts.

An unique construction of the band saw machine with three pulleys for leading of the blade. With the blade that is 8 grades sloped against the level guarantee high-efficiency of cutting.

Highly efficient machine for cutting of construction steel of profile type. Secondary can be used for hardened material cutting.

Control system:

- Machine is equipped with programmable PLC SIEMENS SIMATIC S7-1200. Drive of band blade, movement of arm and movement of feeder are completely controlled and drive by SIEMENS technology.
- The coloured touch screen HMI SIEMENS TP 700 COMFORT enables easy communication with an operator. It shows working conditions (blade speed, moving to the cut, cutting parameters etc.)
- The machine enables to work with two modes:
 - SEMIAUTOMATIC CYCLE: The machine cuts the material immediately in a semiautomatic mode. The operator uses the feeder of the machine for the manipulation with the material and for the exact feed of the material into the cutting zone. The movement of the feeder is realized by manual buttons or by GTO function. After starting GTO function the operator sets the position of the feeder, presses START GTO button and feeder goes to the set position.
 - AUTOMATIC CYCLE: the feeder feeds the material according to the set programm. The operator sets the cutting programm, machine realizes these programmes, it is possible to make thousand different programmes. The part of one programm is a complete setting of the cut: blade speed, feed speed, setting of an automatic regulation, setting of the height of the bar to be cut, setting of the length of the bar, angles values and number of pieces. The length and number of pieces it is possible to set in 20 lines, the machine feeds differently set lengths automatically.
- Regulation of cutting feed is realized by controlled system by the servo-motor and throttle valve of hydraulic. Then is reached very precise cutting feed. Operator will input into program required cutting feed (mm/min) and bandsaw this cutting feed precisely set.
- Two basic regimes of automatic system regulation (ASR): ARP a RZP.
 - RZP = Zone regulation. System enable to cut material in 5 zones, because of setting optional cutting feed and blade speed according on blade position.
 - ARP = System of the automatic regulation of the cutting feed rate depending on the cutting resistance of the material or blunting the blade. System offers two basic modes of ARP: BIMETAL and CARBIDE.
 - BIMETAL mode is suitable for optimization of the cutting feed when cutting profiles by bimetal blades. The cutting feed is higher if the blade cuts sides of the profile. As the blade reaches the full material, the system reduces the cutting feed automatically so that teeth gap of the blade would not be filled.
 - CARBIDE mode is suitable for cutting of full bars. If the blade is old (blunt), loaded is the cutting feed reduced Reaction time is slower than in mode BIMETAL.
- The control panel is equipped with mechanical buttons and digital display of the machine control system. Mechanical buttons controls basic saw movements (arm, vice, feeder) and cutting cycle start. The safety button is present on the panel aswell. Buttons for controlling the movements of the machine are part of a high-quality foil keyboard. Safety module with autodiagnosics.

Construction:

- The machine is constructionally designed in that way, so that it corresponds to extreme exertions in productive conditions.
- The arm of machine with columns situated as near the clamping vice as possible minimizes vibrations and enables max. cutting performance.
- The arm of the machine is robust, heavy weldment and it is designed so that a toughness and a precision of cut was ensured.
- The arm moves along two columns using a four row linear leading with a high loading capacity. Arm movement using two hydraulic cylinders.
- 3 pulleys from cast iron are used.
- The arm uses incremental sensor for evaluation of current position above material. Upper working position of the arm is possible to set in control system.
- Down working position is set with adjustable mechanical stop and microswitch. Down working position of the arm is also possible to set in the saw control system. After reaching bottom working position the arm stops in the position set in the system.
- Main vice is massive steel weldment. Its jaws are iron casting.
- Hydraulic, long stroke main vice. Jaws enable well clamping of material.
- Jaws of the main vice move on two rails of linear leading using hydraulic cylinder. One jaw is longstroke (the movement by longstroke hydraulic cylinder), one is fixed.
- Regulation valves for setting a vice pressure in hydraulic system.
- Very firm feede is moving along 4-rails linears. The feeder movement is provided by bevel gear box, cogwheel and geared rack.
- Transporter is driven by electric engine with mechanical brake and frequency convertor.
- Indication of actual position by incremental sensor, which reads operating speed of gearbox output shaft.
- Indication of material in the feeder: optic sensor - it notices that there is a material in the feeder. If there is no material in the feeder, the signal reflects on the glass that is situated on movable jaw and it goes back to the sensor. The machine stops feeding and waits for another bar.
- The roller conveyer goes through the whole machine and supports the material in all its length. The roller conveyer of the feeder : bearings houses of the rollers are mounted into the basement – big robustness and precision.

- The feeder (transporter) has its own hydraulic unit.
- The feeder clamping vice is a robust steel weldment. Jaws ensure safe clamping of the material.
- Jaws of the feeding vice move along two-rails linears using hydraulic cylinder. One jaw is long stroke (the movement by longstroke hydraulic cylinder). Second jaw is short stroke (utilization during bar feeding: not jaw wearing out, not slipping of material). Short stroke jaw is suitable for feeding of deformed material.

Basic equipment of machine:

- The blade leading in guides with hardmetal plates and leading bearings and along cast iron pulleys.
- The blade is 8 grades sloped regarding the level of the vice => higher performance when cutting, profiles, longer blade life, higher performance when cutting full materials.
- There is a guide situated on the firm beam on the drive side. On the tightening side there is the guide situated on the moving beam.
- The guide beams of moving band guide is adjustable in whole working range. Manual adjustment and fixing of the guide beams.
- Hydraulic tightening of band.
- Automatic indication of blade tension.
- A cleaning brush is driven by an electroengine and ensures perfect cleaning of a blade.
- There is a planet gear box drive and a three-phase electroengine, a fluent regulation of a blade speed by a frequency converter for a fluent change of blade speed.
- The cooling system for emulsion, led to the guides of the blade and by LocLine system directly to the cut groove.
- Massive base with a tank for chips. Base is designed for manipulation with machine by crane.
- Indication of blade tightening and opening of the cover.
- Controlling 24 V.
- Machine is equipped with hydraulic system which controls all functions of that machine. It pushes the arm to cut, pulls up the arm, opens and closes vices, moving of feeder.

Basic accessories of machine:

- Lighting of work space.
- Band saw blade.
- Set of spanners for common service.
- Manual instructions in electronic form (CD).

Operating cycle:

After starting the machine, vices clamp after starting the machine, the machine makes the cut by a set speed, the cutting zone in the down position of the arm is released - the longstroke jaw of the firm vice open, the feeder moves the material to the firm vice, the arm lifts up to the set upper position. The material is moved by the feeder – periodic regime (feeder moves between zero position and the position of the set length of feed) or consecutive regime (feeder moves to the limit position and clamps the material and feed it to the cut consecutively). The main vice clamps the material, the vice of the feeder is still closed and the whole procedure repeats. The operator only loads the material and removes the cut material. It is possible to regulate the cutting speed of the arm and the blade speed during cutting.

cutting parameters

		 0°	 b	
	D [mm]	1000	x	
	D [mm]	550*	x	
	axb [mm]	1000x960	1000x650	

* Recommended values. Recommendations of band blade producers are to be followed when choosing to cut full material, their dimensions are limited by available size of the teeth for the specific type of the band.

° Cutting of the bundle without upper vice HP. HP = accessory for additional price. The cutting parameters are limited when using.

performance parameters

drive of the blade	kW	7,5
drive of the hydraulic agregate	kW	4,0
pump of the cooling emulsion	kW	0,155
electroengine of the cleaning of the blade	kW	0,12
drive of feeder	kW	3,0
total input (Ps)	kW	20,9
cutting speed – fluently set	m/min	20-100
diameter of the blade	mm	8920x54x1,6
electric connection		3x400V, 50 Hz, TN-S

control

feed of the Frame to the cut	Hydraulically
feed of the material	Electrically driven feeder is moved by support cylinders and linear leading.
clamping of material	Hydraulically
bend tension	Hydraulically
cleaning of the blade	A cleaning brush is driven by an electroengine

parameters

length	width	Height		height of the table	weight
		[Hmax]	[Hmin]		
[L]	[B]	[Hmax]	[Hmin]	[V]	(kg)
5050	7200	3700	2960	815	9500

